Errata

Erratum: Scattering Parameters Representing Imperfections in Precision Coaxial Air Lines

Donald R. Holt

National Institute of Standards and Technology, Boulder, CO 80303

[J. Res. Natl. Inst. Stand. Technol., Volume 94, Number 2, March-April 1989, p. 117]

The following errors were found in this paper: On page 121, eq (2.7b) should read:

$$\frac{\mathrm{d} A_{00}^{-}}{\mathrm{d} z} - j\beta A_{00}^{-} = -\frac{1}{2} \frac{1}{\ln \frac{b(z)}{a(z)}} \left\{ \frac{b'(z)}{b(z)} - \frac{a'(z)}{a(z)} \right\} A_{00}^{+}.$$

On page 121, the equation immediately above eq (3.2c) should read as follows:

$$C_{k-1}(0) = \hat{C}_{k-1}(z_{k-1})$$
.

On page 121, the sentence immediately below eq (3.2c) should read:

such that $C_{0,k-1}$ represents the measurement of a(z) or b(z) at $z = z_{k-1}$.

On page 122, eq (3.8) should read:

$$A_{00}^{-}(0;z) = A_{00}^{-}(0;z_1) - A_{00}^{+}(0;z_1) \{e^{-j\beta z_1}\}^{z-z_1} \dots$$

On page 129, the sentence immediately below eq (A.11) should read:

Substituting
$$E_r = \tan{\{\phi_a(z)\}} E_z \dots$$

On page 133, eq (D.3) should read:

$$\ell_0 = \sum_{n=0}^{N-1} \dots .$$